

ROPAK™ Pallets

an eco-friendly alternative to wood



ROPAK 3230 Pallet

4-Way Fork Entry

A	2.13"/54.10 mm	E	5.88"/149.23 mm
B	12.36"/313.99 mm	F	13.00"/330.20 mm
C	19.89"/505.16 mm	G	17.25"/438.15 mm
D	3.44"/87.33 mm	H	2.25"/57.15 mm



ROPAK 4048 Pallet

A	7.62"/193.50 mm	E	5.49"/139.47 mm
B	20.65"/524.43 mm	F	16.91"/429.56 mm
C	26.96"/675.56 mm	G	22.56"/573.00 mm
D	3.47"/88.11 mm	H	3.47"/88.11 mm



ROPAK 4548 Pallet

A	6.94"/176.28 mm	E	8.75"/222.35 mm
B	17.26"/438.38 mm	F	18.53"/470.56 mm
C	30.74"/780.85 mm	G	26.47"/672.44 mm
D	3.61"/91.67 mm	H	3.61"/91.67 mm

Pallets Available in a Variety of Sizes

Other pallet sizes can be fabricated. Please call Customer Service at 1.800.442.4892 for details.

ROPAK 3230 PALLET SPECIFICATIONS

Part Number		3230P0 flat surface	3230P0¹ flat surface
		4-way entry	2-way entry/conveyable
Exterior Dimensions	length	32"/813 mm	32"/813 mm
	width	30"/762 mm	30"/762 mm
	height	5.6"/142 mm	5.6"/142 mm
	height with lip	N/A	N/A
Interior Dimensions	length	N/A	N/A
	width	N/A	N/A
Load Capacity	Static	30,000 lb	30,000 lb
Tare Weight (may vary)		22 lb/10.0 kg	23 lb/10.4 kg
Truckload Quantity	48'/53'	864/960	864/960
40' ISO Container	Standard/Hi Cube	588/672	588/672

21

3230 Pallet options include a 1" lip or a flat surface, Closed Deck or Open Deck.

ROPAK 4048 PALLET SPECIFICATIONS

Part Number		4048P0 flat surface	4048P1 with 1" lip
		4-way entry	4-way entry
Exterior Dimensions	length	47.3"/1201 mm	47.3"/1201 mm
	width	39.4"/1001 mm	39.4"/1001 mm
	height	5.7"/145 mm	N/A
	height with lip	N/A	6.7"/170 mm
Interior Dimensions	length	N/A	43.6"/1107 mm
	width	N/A	36"/914 mm
Load Capacity	Static	30,000 lb	30,000 lb
Tare Weight (may vary)		48 lb/21.8 kg	52 lb/23.6 kg
Truckload Quantity	48'/53'	448/480	448/480
40' ISO Container	Standard/Hi Cube	294/336	294/336

4048 Pallet options include a Closed Deck or Open Deck.

ROPAK 4548 PALLET SPECIFICATIONS

Part Number		4548P0 flat surface	4548P1 with 1" lip
		4-way entry	4-way entry
Exterior Dimensions	length	48"/1219 mm	48"/1219 mm
	width	45"/1143 mm	45"/1143 mm
	height	5.7"/145 mm	N/A
	height with lip	N/A	6.7"/170 mm
Interior Dimensions	length	N/A	44.2"/1123 mm
	width	N/A	41.5"/1054 mm
Load Capacity	Static	30,000 lb	30,000 lb
Tare Weight (may vary)		52 lb/23.6 kg	56 lb/25.4 kg
Truckload Quantity	48'/53'	384/416	384/416
40' ISO Container	Standard/Hi Cube	252/288	252/288

¹ This model has a 2-way conveyable base.

All dimensions and specifications are approximate. Tare weight will vary based on color and size. Performance characteristics are based on uniform static loads and may be affected by concentrated loads and elevated temperatures. HDPE materials and workmanship guaranteed for 3 years.

56" x 44" Footprint Reusable Bulk Pallets are Perfect for:


Beverage Cans | Composite Cans | Metal Cans
PET Bottles | General Bulk Applications

LINPAC's 4456 Bulk Pallet designed for lighter loads



22

4456 Bulk Pallet



A	7.51"/190.86 mm	E	5.86"/148.77 mm
B	20.99"/533.04 mm	F	18.02"/457.81 mm
C	35.01"/889.36 mm	G	25.98"/659.79 mm
D	0.75"/19.05 mm	H	0.75"/19.05 mm

4456 BULK PALLET SPECIFICATIONS

Part Number	4456	
	flat surface	
	4-way entry	
Exterior Dimensions	length	56"/1422 mm
	width	44"/1118 mm
	height	4.4"/111 mm
Load Capacity	Static	30,000 lb/13607 kg
	Dynamic	4000 lb/1814kg
Tare Weight (may vary)	51 lb/23.2 kg	
Truckload Quantity	48'	528
	53'	550
Design/Construction	One-piece	

The **4456 Bulk Pallet's** design incorporates *Smart Deck Technology™* to create a flat, smooth surface that resists deflection and warping. Sloped lip transitions ensure leg and leg strap integrity.

Additionally, the 4456 Bulk Pallet's hygienic, flow-through deck design means that surface openings are perfectly aligned to underside openings. This allows both contaminants and wash water to easily fall through the openings, rather than collect on surfaces, for a bacteria-free, fast-drying pallet.

The 4456 Bulk Pallet has been approved by the FDA as meeting sanitary requirements for packaging handling in food and beverage applications.

Please call Customer Service at 1.800.442.4892 for more information.

All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected by concentrated loads and elevated temperatures. Materials and workmanship guaranteed for 3 years. Material: High Density Polyethylene.